



#07



TECHNICAL SPECIFICATIONS

PRODUCT INFORMATION

Productnorm	EN ISO 10582	
Level of use	EN ISO 10874	23 - 32 - 42*
Total thickness	EN ISO 24346	2,5 mm
Wear layer	EN ISO 24340	0,55 mm
Wear layer PUR treatment		Superguard Pro®
Total weight g/m²	EN ISO 23997	4063 g/m³

SIZE & PACKING

Planks	EN ISO 24342	19,6 x 132,0 cm
Box planks	14 pcs/box	3,622m²/box
Tiles	EN ISO 24342	32,9 x 65,9 cm
Box tiles	16 pcs/box	3,469m²/box

TEST RESULTS

Inflammability	EN 13501-1	Bfl-S1
Squareness & straightness	EN ISO 24342	≤ 400 mm: ≤ 0,25 mm > 400 mm: ≤ 0,35 mm
Slip resistance	EN 13893	DS
Slip restraint	EN 16165:2021-10 Annex B	≥ R9
Residual indentation	EN 24343-1	Average result measured: 0,05 mm
Furniture leg resistance	EN 424	No damage
Curling	EN ISO 23999	Norm: ≤ 1 2 l mm Result: ≤ 2 mm
Dimensional stability	EN ISO 23999	Norm: ≤ 0,25 % Average result measured: ≤ 0,05 %
Heat insulation	EN ISO 10456	0,25 w/(m.K)
Thermal resistance R	EN 12667	0,01 m².K/W
Formaldehyde group	EN 717-1	E1
Acoustic insulation	EN 10140-1/3	Δ Lw ≥ 4 dB
Acoustic insulation + Flex Pro underlay	EN 10140-1/3	Δ Lw ≥ 8 dB
Castor chair resistance	EN 425	No damage to wearlayer, no delamination
Stain resistance	EN 438-2	Grade 5
Light fastness	ISO 105-B02:2014	≥ 6
Underfloor heating		Suitable, max 27°C
Warranty (year)		25 Residential 10 Commercial*

The warranty covers manufacturing defects and premature wear in the event of normal use.
* Only applicable for a fully glued installation

